

# Instruction for TAC Vector Optics Harrier 1x22 Red Dot Scope



**WARNING:** NEVER LOOK AT THE SUN THROUGH THE RIFLESCOPE (OR ANY OTHER OPTICAL INSTRUMENT). IT MAY PERMANENTLY DAMAGE YOUR EYES.

## MOUNTING

The scope is installed on gun by means of a mount. Simply loosen the weaver base knob and place the scope over the weaver or picatinny rail on your rifle. Fasten the screw to fix it firmly.

## PRECISION ADJUSTMENTS

Remove windage and elevation adjustment screw covers. Before adjust make sure the scope is mounted on the gun on a solid support. Windage is the horizontal (left-to-right) adjustment, usually the side turret of the scope. Elevation is the vertical (up-and-down) adjustment, usually the top turret of the scope.

The scopes feature 1/2 M.O.A. (1/2" at 50 or 100 yards according to the factory setting) windage and elevation adjustment with audible clicks. Each click of adjustment changes bullet strike at a shooting distance by the amount indicated.

## BATTERY EXCHANGE

Your red dot scope is power by 3V lithium battery 2032. To install or replace the battery, unscrew the top cover of battery compartment and insert the battery ('+') positive side up.

## SEALED WATERPROOF AND FORPROOD

The scope is with O-ring to prevent the entry of dust or moisture.

## MAINTENANCE

Your riflescope, though amazingly tough, is a precision instrument that deserves reasonable cautious care.

1. When cleaning the lens, first blow away any dirt and dust, or use a soft lens brush. Fingerprints and lubricants can be wiped off with lens tissue, or a soft clean cotton cloth, moistened with lens cleaning fluid.
2. All moving parts of the scope are permanently lubricated. Do not try to lubricate them.
3. No maintenance is needed on the scope's outer surface, except to occasionally wipe off dirt or fingerprints with a soft cloth.
4. Use lens covers whenever convenient.

## STORAGE

Avoid storing the scope in hot places, such as the passenger compartments of vehicles on hot days. The high temperatures could adversely affect the lubricants and sealants. A vehicle's trunk, a gun cabinet or a closet is preferable. Never leave the scope where direct sunlight can enter either the objective lens.

Damage may result from the concentration (burning glass effect) of the sun's rays.

**TAC Vector Optics**

[www.scvector.biz](http://www.scvector.biz) [www.scvector.com](http://www.scvector.com)

