

Instructions for Vector Optics Sphinx 1x22 Red Dot Sight



This tubeless design reflex lens aperture provides a wide field of view. It is smaller and lighter than any other sighting device, which is suitable for rapid-firing or moving targets shooting.

Automatic red dot brightness system offers the integrated control circuit adjusts the brightness of the aiming dot to varying light levels in the surrounding environment.

Specification

Magnification: 1x

Reticle: Auto brightness sense red dot

Size: 48Lx25Wx37Hmm

Weight: 55g (2 Ounce)

Unlimited eye-relief

Build-in weaver mount

Fittings: Screw driver, hex key and spare battery etc

MOUNTING

The scope is installed on gun by means of a mount. Simply loosen the weaver base knob and place the scope over the weaver or picatinny rail on your rifle. Fasten the screw to fix it firmly on the rifle.

PRECISION ADJUSTMENTS

Before adjusting the precision, make sure to use the screw driver to loosen the two locking screws in the back of the scope. To avoid the internal mechanical damage use the flat screw driver to adjust elevation and windage screws. Finally fasten the two locking screws to fix the reticle.



BATTERY EXCHANGE

To exchange the CR2032 battery, just use the supplied hex key to loosen the two upside screws. Take apart the scope from the weaver mount base. Take out the used battery, exchange with a new one and then assemble the scope.

SEALED AND WATERPROOF

The scope is with O-ring to prevent the entry of dust or moisture.

MAINTENANCE

Your riflescope, though amazingly tough, is a precision instrument that deserves reasonable cautious care.

1. When cleaning the lenses, first blow away any dirt and dust, or use a soft lens brush. Fingerprints and lubricants can be wiped off with lens tissue, or a soft clean cotton cloth, moistened with lens cleaning fluid.
2. All moving parts of the scope are permanently lubricated. Do not try to lubricate them.
3. No maintenance is needed on the scope's outer surface, except to occasionally wipe off dirt or fingerprints with a soft cloth.
4. Use lens covers whenever convenient.

STORAGE

Avoid storing the scope in hot places, such as the passenger compartments of vehicles on hot days. The high temperatures could adversely affect the lubricants and sealants. A vehicle's trunk, a gun cabinet or a closet is preferable. Never leave the scope where direct sunlight can enter either the objective or the eyepiece lens. Damage may result from the concentration (burning glass effect) of the sun's rays.

ALWAYS KEEP THE MUZZLE POINTED IN A SAFE DIRECTION.

TACVector Optics

www.scvector.biz www.vectoroptics.com

